



HAULER[®] 800

UNMATCHED PRODUCTIVITY STARTS HERE.

The Hauler 800, now available with an ELiTE lithium powertrain activated by Samsung SDI battery technology or with a fuel-efficient 13.5 hp EFI gas engine, powers through your toughest workdays. With a fully customizable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 vehicles have everything you need to finish job after job.

ELiTE
LITHIUM

CUSHMAN.COM

8.4 CU FT
CARGO BED

900 LB
TOWING CAPACITY

800LB
VEHICLE LOAD CAPACITY

2 PASSENGER
SEATING

ZERO MAINTENANCE
ELiTE LITHIUM BATTERY



ELiTE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Multifunction SOC/Speedometer Gauge

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger (ELiTE Only)
- Fuel/Oil Gauge (Gas Only)

CUSHMAN.COM

HAULER® 800

BODY & CHASSIS

	HAULER 800 ELiTE	HAULER 800 GAS
FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	

DIMENSIONS

OVERALL LENGTH	110 in (279.4 cm)	
OVERALL WIDTH	49 in (125 cm)	
OVERALL HEIGHT	47 in (119.4 cm) (No Canopy) 69.5 in (176.5 cm) (w/ Struts & Roof)	
WHEEL BASE	65.5 in (166.4 cm)	
WHEEL TRACK	37 in (94 cm) Front / 38 in (96.5 cm) Rear	
GROUND CLEARANCE	4.3 in (10.9 cm)	
CARGO BOX CAPACITY	8.4 cu ft (0.24 cu m)	
CARGO BOX DIMENSIONS	28.5 in (L) x 44.5 in (W) x 12 in (D) (72.4 cm x 113 cm x 30.5 cm)	
CARGO BOX MATERIAL	Roto-Molded Polyethylene	

POWER

POWER TRAIN	56.7V Li-Ion Battery	4-Cycle, 24.5 cu in (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	11.7 hp (8.7 kW) Peak	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxilliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPER)	2.2 Elite - Single Pack	One, 12V Maintenance Free
KEY OR PEDAL START		Pedal
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE		Differential w/ Helical Gears
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	753 lb (342 kg)	761 lb (345.2 kg)
CURB WEIGHT	800 lb (363 kg)	791 lb (359 kg)
VEHICLE LOAD CAPACITY	800 lb (362.9 kg)	
BED LOAD CAPACITY	400 lb (181.4 kg)	
TOWING CAPACITY	900 lb (408.2 kg)	
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	18 x 8.5 -8 (6 Ply Tires)	

Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model. California state law prohibits the sale of Model Year 2024 and later gas-powered carts. ©2023 Textron Specialized Vehicles Inc. 82288-G12 (Rev. 05/2023)

